

MATERIAL SAFETY DATA SHEET
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S DEPARTMENT OF LABOR
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB. No. 1218-0072

IDENTITY (As used on Label and List)

LubeAID

SECTION I

Manufacturer's Name: CTECH

Emergency Telephone Number: Ctech
INT'L: +4792899969

Address
Overby,3531 Krokkleiva

Telephone Number for information: +4792899969

Chemical Name and Synonyms: Petroleum Grease

Trade Name and Synonyms: Metal Based Grease Lubricant

Chemical Family: Petroleum Grease

Formula: N. A.

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name (s))	OSHA PEL	ACGIH TLV	%(optional)
Solvent Petroleum Hydrocarbon		70	
Additives: Micrometallic particles		30	.2 mg/m3

SECTION III - Physical /Chemical Characteristics

Boiling Point: 700°F
Vapor Pressure: N. A.
Vapor Density(AIR = 1) N. A.

Specific Gravity (H2O = 1.36):
Melting Point:
Evaporation Rate: (n-BuAC=1) N. A.

Solubility in Water: Insoluble

Appearance and Odor: Bronze to brown.

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used) : Open Cup 400°F
Flammable Limits - LEL: Unknown UEL: Unknown

Extinguishing Media: Regular foam, dry chemical, carbon dioxide.

Special Fire Fighting Procedures: Water may cause frothing which can be violent and possibly endanger the lives of fighters.

Unusual Fire and Explosion Hazards: NONE

OSHA -174, Revised Sept.1985

NFPA (NATIONAL FIRE PROTECTION ASSOCIATION STANDARD)
Health Hazard: 1 Flammability: 1 Reactivity: 0

